

Mini-Bank

# NH-2100T



The Best Value in retail through-the-wall ATM, the NH-2100T offers flexibility for installation with its efficient design

## Features

- **Reliability**

NH-2100T meets security standards such as Triple DES compliance and a VISA Encrypting PIN pad. Transreflective LCD display and weatherized construction ensures operation in all climates.

- **Flexibility**

Compact architecture with ergonomic design offers unrivalled flexibility for installation and mounting in all environments.



*Create your true ATM values  
Design your own portfolio*



The **NH-2100T** provides outstanding flexibility and reliability to satisfy your requirements.

The **NH-2100T** supports exceptional reliable performance with various components such as standard 2000 note capacity cash dispenser and service panel for monitoring, configuration, diagnostics and maintenance.

Our solution strengthens you to build better customer relationships as well as enhanced technologies

**Nautilus**  
HYOSUNG

*Nautilus Hyosung, always by your side*



### Customer Display

5.7" Monochrome Transreflective LCD

### Communication

Dial-up

#### Optional

TCP/IP

### Input Type

4 x 2 Function keys

4 x 4 Numeric keys

Encrypting PIN Pad

(DES, T-DES, Unique Key)

### Supervisor Operation

Customer display in common

#### Optional

Service panel

5.7" mono display

4 x 2 function keys, 16keys

### Card Handling

Dip type card reader

#### Optional

IC card reader

### Cash Dispensing

2000 note cassette

200 notes reject bin

### Printers

Thermal receipt printer

### Security

UL291 business hour vault

Dial Lock

#### Optional

Electronic Safe Lock

KABA Mas Cencon Safe Lock

### Miscellaneous

Illuminated signage

#### Optional

Adjustable pedestal

### Power Supply

AC 110~230V, 50~60Hz

### Operating Environment

Temperature

40°F~95°F (5°C ~ 35°C)

Humidity

15%~85%

### Dimension and Weight

Height : 31.5" (800mm)

Width : 20" (508mm)

Depth : 28.5" (724mm)

Weight : 283 lbs (128kg)

Wall thickness : 4" ~ 10"

※ New technologies and components may be implemented in the products without prior notice, so Nautilus Hyosung reserve the right to change specifications accordingly.



**Head office)** 52 Cheongdam-Dong, Gangnam-Gu, Seoul, Korea 135-100

TEL:+82-2-510-0441, FAX:+82-2-3442-7993, <http://www.nautilus.hyosung.com>

**Nautilus**  
HYOSUNG

**US office)** William Square Center #218, 5205 North O'CONNOR Blvd, Irving, TX 75039

TEL:972-443-9820, FAX:972-443-9821